

STACK100

The DYNESS STACK100 energy storage system is widely used in energy storage sector. It adopts modular design and can be used for residential and C&I applications. The reliable LiFePO4 technology ensures maximum safety and a longer life cycle.



Each PACK has an independent fire extinguishing device.



1C discharge, built-in air-cooling system



Single system capacity:
15.36-76.8kwh, expandable to a maximum of 957.6kWh in parallel



Convenient installation and
Total installation time ≤1h



Flexible space layout ability

System parameters

Model	STACK100
Battery Type	LiFePO4
Module Voltage/Capacity	51.2V/100Ah
System Modules Serial Number	3~15
System Energy Range	15.36~76.8kWh
Operating Voltage	134~876V
Recommended Charge/Discharge Current	50A (0.5C)
Max. Charge/Discharge Current	100A (1C)
Peak Discharge Current(2min 25℃)	125A(1.25C)
Depth of Discharge	95%
Communication	CAN/RS485
Cycle Life	Unlimited Cycles / 10 Years
Signal Module Weight	47Kg
Max. Single Cluster Dimension[W*D*H]	591*390*1700mm – 11 module
Charging Temp. Range	0 ~ 55℃
Discharging Temp. Range	—20 ~ 55℃
Protection Level	IP20
Fire Protection System	Aerosol fire extinguisher
Installation method	Stack type
Cooling method	Forced wind cooling
WIFI Module	Built-in WIFI module; APP OTA Function
Certification & Safety Standard	CE-EMC/CE-RED/62619/63056/62477/62040 /UN38.3
Compatible Inverters	Deye/Goodwe/Solis/SAJ/Sinexcel/Hoymiles/Growatt/Ecatus/Sermatec/ATESS/Sunways etc.